

AWC DC-208

Dechlorination Chemical for Membrane Systems

ADVANTAGES

- Odorless dechlorination chemical used to remove free and combined chlorine from reverse osmosis (RO) feedwaters
- Prevents severe oxidation and free-radical damage to RO/NF membranes by reducing dissolved chlorine into the non-reactive chloride ion
- Effectively converts all oxidizers such as ozone, chlorine dioxide and hydrogen peroxide to non-reactive species
- Deactivates biocides such as isothiazoline and DBNPA
- Stabilized to maintain active contents for long storage times. Does not emit toxic SO₂ gas.
- Higher rate of reaction with chlorine and better efficiency than bisulfite solutions or activated carbon
- Certified by NSF to NSF/ANSI Standard 60

TYPICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Odor	Pungent
Solubility in Water	Complete
Specific Gravity	1.35 ± 0.05
pH (as is) @ 25°C	5 - 7

PACKAGING

5 gallon pails, 55 gallon non-returnable plastic drums

SAFETY & HANDLING

May be toxic by ingestion. If ingested, drink at least two (2) glasses of water and get medical attention. Contact with eyes causes severe irritation or burns. If eyes are contacted, immediately flush with clean water for 15 minutes and then get medical attention. For skin contact, wash with soap and water. This product is a reducing agent. Always store away from oxidizers. For more information, see the Safety Data Sheet provided with this product.

CHEMICAL FEEDING AND CONTROL

Normally fed continuously prior to the final cartridge filter. It should be injected by chemical dosing pump from a dilution tank or directly from the drum to the feedwater line. Steel, stainless steel, or plastic may be used in the chemical feed system. Copper, copper alloys and aluminum metallurgies for chemical feed system must be avoided.

